

# C.A.M

CONSISTENT | ACTIVE | MOBILE

 **PLACER**  
KING LONG *high roof*

Available in :



### 2.4L 4RB2 Petrol Engine

A unique 2.438 L petrol engine with 16-valve Double Overhead Camshaft developed by new Japanese technology with integration of international advanced technology for commercial & private demands.



### 2.8L Turbo Diesel Engine

A mature diesel engine utilizing the Japanese Technology. With high power, high torque & high reliability, this engine has low fuel consumption which makes it an efficient business vehicle.

**Powerful | Long Lasting | High Fuel Efficiency**

**MARKET LEADER OF CHINA VAN TRUSTED BY OVER THOUSANDS OF CUSTOMERS SINCE 2009**



**FACELIFTED CAM PLACER**  
*Still economy, now with:*



Projection Head lamp & LED Light



Fully Reclinable Seat Bed with Side Shift\*



Digital Panel Meter (Available Diesel Only)



Sport Rim (Optional Accessories)

# PLACER high roof

# 2.4L PETROL

# 2.8L DIESEL



Modern Dashboard with 4-Spoke Tilt Adjustable Power Steering Wheel



Spacious Passenger Seat



Middle Console Box



Switchblade Key with Remote Control



Side Mirror with Signal Lamp & Daylight




Modern Design Foglamp

Branch / Dealer Chop :



ENGINE	4RB2	JE493ZQ4A
Engine Model		
Engine Type	In Line 4 Cylinder Double Overhead Camshaft, 16 Valve Petrol Engine	4 Cylinders, Water-Cooled, Direct Injection, Turbo Diesel
Bore x Stroke	95 x 86	93 x 102
Fuel Standard	Petrol	Euro-II Diesel
Displacement (L)	2438	2771
Rated Output (KW/HP/rpm)	102/4600-5000(136.8)	70(93.9)/3600
Maximum Torque (N.m/rpm)	217/2600-3200	225/1600-2600
Compression Ratio	9.2	17.5
Top Speed* (km/h)		+ 120
Fuel Tank Capacity (L)		70
DRIVING SYSTEM	Manual 5-Speed	
Transmission Type		
Rear Axle Ratio	Gear Ratio	1st: 3.992   2nd: 2.15   3rd: 1.334   4th: 1.00   5th: 0.757   Reverse: 4.22
Drive Type	4.3	4.1
Brake System	Front engine, rear drive	
Suspension	Front disc & rear drum, ABS+EBD	
Steering System	Torsion bar with parallel leaf spring	
TECHNICAL DIMENSION	Mechanical hydraulic power steering	
Overall LxWxH (mm)	5200 x 1700 x 2250	
Wheelbase (mm)	2890	
Ground Clearance (mm)	150	
Gross Vehicle Weight (kg) (BDM)	3500	
Curb Weight* (kg) (BTM)*	1845	
Seating Capacity	14 seats (2+3+(2+1)+(2+1)+3)	
Tyre Size	195/70R15	
Wheel Type	15" Alloy	
Minimum Turning Radius (m)	6	
EXTERIOR		
Hallogen Projection Headlamp	•	
Front Fog Lamp	•	
LED Turning Signal Lamp	•	
Power Side Mirror with Signal Lamp and Daylight	•	
Rear Windsreen with Demister	•	
Rear Wiper with Washer	•	
INTERIOR		
Anti-glare Rear View Mirror	•	
Power Window - Driver & Co-Driver	•	
Middle Console Box with 2 Cup Holder	•	
Audio System	DVD + reverse display with reverse sensor	
Central Locking with Integrated Remote Key System	Switchblade key with remote control	
Sliding Window	Rear	
Seat Material	Fabric	
Seat Type	Fully reclinable seat bed with side shift* ; Foldable last row for larger storage space	
Sliding Door	1 (left)	
Rear Air Conditioning System	Vents at side of cabin roof	
SAFETY SYSTEM		
Safety Belt	Driver: 3- Points with Pre-Tensioner, Co-Driver: 3-Points with Pre-Tensioner, Rear Passenger: 2 Points	
ABS+EBD	•	
High Mounted 3rd Brake Lamp	•	

\*Data collected under testing conditions. The final results may differ due to different driving conditions, overall vehicle weight etc.



Sendok Group  
www.sendokgroup.com

Disclaimer: All features & specification shown in this brochure are subject to change without prior notice and may vary according to locality. The colour(s) of the vehicle(s) and the interior shown herein may slightly differ from actual vehicle.